



### Product Features

**H1024 - 2.4 GHz      H2024 - 2.4 GHz**

#### Description

The TACO models H1024 and H2024 circular polarized helical antennas are enclosed with a polycarbonate radome for protection from the environment. Choose our anti-static coating for mining applications. The higher gain H2024 is available in right-turn or left-turn helix. Both models include a mast mount, and wall and ceiling mounting is also available as an accessory (CM-1). These antennas are ideally suited to harsh environments that have severe reflections from metal surfaces and water.

#### Application

Wi-Fi, ISM, RFID, VOiP, warehousing, tunnels, mining applications, elevator shafts, video surveillance, downtown corridors, parking lots, wireless security cameras.

### ELECTRICAL SPECIFICATIONS

MODEL	H1024	H2024
FREQUENCY - GHz	2.4 - 2.5	2.4 - 2.5
GAIN - dBic	13.8	17.4
POLARIZATION	RHCP	RHCP
HPBW - °	35	24
F/B RATIO - dB	36	31
VSWR	1.5:1	1.5:1
IMPEDANCE - Ohm	50	50
TERMINAL TYPE	N Female	N Female
MAXIMUM INPUT POWER - W	50	50

### MECHANICAL SPECIFICATIONS

MODEL	H1024	H2024
LENGTH - in (cm)	13.1 (33.3)	30.1 (79.5)
GROUND PLANE DIAM - in (cm)	5.5 (13.8)	5.5 (13.8)
HOUSING	Polycarbonate	Polycarbonate
WEIGHT - lbs (kg)	1.2 (0.5)	1.6 (0.7)
MOUNTING OD - in (cm)	1.625 (4.1) Mast or Wall	1.625 (4.1) Mast or Wall

Wade Antenna's ongoing policy of continuing development may result in specification changes to its products.